

Compact, Yet Powerful

The ECOSYS PA4500x is a powerful printer embedded with high-level security features. The rapid speed of up to 45 pages per minute contributes to the enhanced productivity of smaller workgroups. Thanks to long-life components and low energy consumption, it leaves a smaller environmental footprint.



ECOSYS PA4500x



A4 Monochrome printer

Up to 45 pages A4 per minute

1200 x 1200 dpi resolution

A4

Specifications

GENERAL

KYOCERA ECOSYS Laser Monochrome Printer

Operation panel: LCD 21 characters, 5 lines

Type: Desktop

Engine speed: Up to 45 pages A4 per minute;

Duplex print speed: 22.5 page per minute, A4

Resolution: 1,200 x 1,200 dpi

Average Print Volume: 15,000 pages per month.

Maximum Life: 900,000 pages or 5 years.

Warm-up time: Approx. 16 seconds or less.

Time to first print: Approx. 5.3 seconds or less.

CPU: ARM Cortex-A53 Dual core 1.4GHz

Memory: Standard 512MB; Max. 2.5GB (optional)

Standard interfaces: Standard interface: USB 2.0

(Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet

(10BaseT/100BaseTX/1000BaseT), optional Wireless LAN

(IEEE 802.11b/g/n), 2 eKUIO slots for optional internal print

server or SSD hard disc, Slot for optional SD/SDHC Card.

Integrated accounting: 100 department codes.

Dimensions (W x D x H): Without packaging:

380 x 410 x 285 mm (without protrusions);

390 x 416 x 308 mm (with protrusions);

With packaging: 549 x 494 x 420 mm

Weight: Without packaging:

Approx. 14.6kg with bundled toner.

With packaging: 18.5 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing: 605.5 W

Ready mode: 8.4 W

Sleep-mode: 0.5 W

Noise (sound pressure level: ISO 7779/ISO 9296): Printing:

54 dB (A)

Stand-by: 30 dB (A)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality

standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of

max. 0.11 mm. Please use paper recommended by

KYOCERA under normal environmental conditions.

Input capacity: Multi-purpose tray: 100 sheets, 60 to

220 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140

x 210 to 216 x 356 mm), Banner paper up to 915 mm.

Standard universal paper cassette: 500 sheet,

60–120 g/m², A4, A5, B5, Letter, Legal, Folio,

Custom (140 x 210 to 216 x 356 mm).

Max. input capacity with options: 2,600 sheets.

Duplex: Standard duplex unit, 60 to 120 g/m², A4, A5, B5,

Letter, Legal, Custom (140x 210 mm - 216 x 356 mm).

Output capacity: 250-sheet-face-down with paper

full sensor.

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible),

PDF Direct Print, XPS Direct Print and Open XPS, PPML,

TIFF/JPEG Direct Print Support, URF, PWG Raster,

PCLm, IBM Proprinter, Line Printer, Epson LQ-850.

Operating systems: All current Windows operating

systems, MAC OS X Version 10.9 or higher, Chrome OS,

Linux, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL6, KPDL3),

4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap

font, 45 types of one-dimensional barcodes, 1

type of two-dimensional barcode (PDF417).

Print features: PDF Direct Print, Internet printing IPP

1.0, E-mail printing, WSD print, secure printing IPP over

TLS, Local and network authentication, Network data

encryption IPsec, HTTPS, LDAP over TLS, SNMPv3,

SMTP over TLS, POP over TLS, Encrypted PDF Direct

Print, Universal Print, Printing for Chrome OS.

Mobile printing support: KYOCERA Mobile Print app

for iOS and Android, AirPrint, Mopria, Wi-Fi Direct.

CONSUMABLES

Average continuous toner yield in accordance with

ISO/IEC 19752.

TK-3404 Toner Kit:

Microfine toner black for 12,500 pages A4.

Capacity of starter toner is 6,000 pages A4.

OPTIONS

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets,

60 - 120 g/m²; A4, A5, B5, Letter, Legal,

Custom (92 x 162 mm - 216 x 356 mm)

PF-3100 Bulk paper feeder and PB-325 Printer base:

Max. 2,000 sheets, 60 - 220 g/m²; A4, A5, B5, Letter,

Custom (76 x 148 to 216 x 305 mm); not to be combined

with PF-3110

CB-360W Cabinet: High Cabinet for 2 draw configuration,

Approx. 380 x 411 x 508 mm (WxDxH)

CB-365W Cabinet: Low cabinet for 4 draw configuration,

Approx. 380 x 411 x 254 mm (WxDxH)

CA-3100 Caster Unit: for increased stability. Mandatory when

installing 4 optional paper feeders.

Memory upgrade: MM-20(1GB)/MM-21(2GB)

Storage Devices for easy document management:

HD-17 SSD hard disk: 64GB

HD-18 SSD hard disk: 256GB

HD-19 SSD hard disk: 512GB

SECURITY OPTIONS

UG-33 AC: ThinPrint support

UG-50: TPM (Trusted Platform Module)

USB IC Card Reader + Card Authentication Kit (B) AC:

Support for various authentication keys available.

CRH 10: IC card Reader Holder

Optional interface:

IB-32 B: IEEE1284 interface

IB-37: Wireless LAN (802.11b/g/n, 2.4-GHz and 5-GHz)

with Wi-Fi Direct

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/1,000

BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

WARRANTY

2 years on-site as standard.

WHAT'S IN THE BOX:

Main unit, pre-installed starter toner, waste toner box, user

documents, power supply cord.

ECOSYS stands for ECOlogy, ECOmy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.



KYOCERA Document Solutions Partner

MARCH2023ECOSYSIPA4500x/VER1.0

KYOCERA Document Solutions Australia

Ph: 13 59 62

www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand

Ph: 0800 459 623

www.kyoceradocumentsolutions.co.nz

